

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES

Oxygen vigorously accelerates combustion. Contact with all flammable materials should be avoided. Some materials which are not flammable in air will burn in pure oxygen or oxygen-enrich atmospheres.

PHYSICAL DATA

| | |
|--|---|
| BOILING POINT -297.3°F (-182.9°C) | LIQUID DENSITY AT BOILING POINT 71.23 lb/ft ³ (1141 kg/m ³) |
| VAPOR PRESSURE @ 70°F (21.1°C) Above the critical temperature of -181.1°F (-118.4°C) | GAS DENSITY AT 70°F 1 atm .0828 lb/ft ³ (1.326 kg/m ³) |
| SOLUBILITY IN WATER Slightly | FREEZING POINT -361.8°F (-218.8°C) |
| EVAPORATION RATE N/A (Gas) | SPECIFIC GRAVITY (AIR=1) @ 70°F (21.1°C) = 1.11 |
| APPEARANCE AND ODOR Colorless, odorless gas | |

FIRE AND EXPLOSION HAZARD DATA

| | | |
|--|---|---|
| FLASH POINT (Method used) N/A | AUTO IGNITION TEMPERATURE N/A | FLAMMABLE LIMITS % BY VOLUME LEL N/A UEL N/A |
| EXTINGUISHING MEDIA Copious quantities of water for fires with oxygen as the oxidizer | ELECTRICAL CLASSIFICATION Nonhazardous | |
| SPECIAL FIRE FIGHTING PROCEDURES If possible, stop the flow of oxygen which is supporting the fire. If cylinders are involved in a fire, safely relocate or keep cool with water spray. | | |
| UNUSUAL FIRE AND EXPLOSION HAZARDS Vigorously accelerates combustion. | | |

REACTIVITY DATA

| | | |
|---|---|---------------------|
| STABILITY Unstable | | CONDITIONS TO AVOID |
| Stable | X | None |
| INCOMPATIBILITY (Materials to avoid) All flammable materials | | |
| HAZARDOUS DECOMPOSITION PRODUCTS None | | |
| HAZARDOUS POLYMERIZATION May Occur | | CONDITIONS TO AVOID |
| Will Not Occur | X | None |

SPILL OR LEAK PROCEDURES

| |
|--|
| STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Evacuate all personnel from affected area. Use appropriate protective equipment. If leak is in user's equipment, be certain to purge piping with an inert gas prior to attempting repairs. If leak is in container or container valve, contact your closest supplier location or call the emergency telephone number listed herein. |
| WASTE DISPOSAL METHOD Do not attempt to dispose of waste or unused quantities. Return in the shipping container properly labeled, with any valve-outlet plugs or caps secured and valve protection cap in place to your supplier. For emergency disposal assistance, contact your closest supplier location or call the emergency telephone number listed herein. |